



| Technical data sheet - PETG REGSHARE filament | |
|---|---|
| Producer | REGSHARE s.r.o. |
| Material | PETG (1,4-Benzenedicarboxylic acid, 1,4-dimethyl ester, polymer with 1,4-cyclohexanedimethanol and 1,2-ethanediol, CAS: 25640-14-6) |
| CLP | Material does not require classification according to Regulation (EC) 1272/2008 |
| Weight | 1 Kg (+/- 50 g) |
| Packaging | Vacuum packed in water, moisture and UV resistant packaging. The packaging is resealable. |
| Diameter | 1.75 mm (+/- 0.05 mm) |
| Colour | white, black, green, orange, blue, brown, grey, yellow, signal yellow, red, natural (transparent) |
| Nozzle temperature | 220-250 °C |
| Bed temperature | 70-90 °C |
| Nozzle | No limitation |
| Viscosity | 0.8 dl/g |
| Softening temperature | 85 °C |
| Melting temperature | 170 °C |

